

BRETFORD BASICS™

ADJUSTABLE PROJECTOR CART WITH CABINET

CA2642NS

Adjusting to multiple heights is as simple as resetting four screws. Pull out notebook shelf and open, roomy shelves provide ample storage space. Lower cabinet stores additional equipment.



FEATURES

- Incorporates your laptop, data projector, DVD player, scanner and more all on one compact presentation cart.
- Features a 5-height capability, from 26-42" h in 4" increments and is easily adjusted by resetting four leg screws.
- Large 14" d notebook shelf pulls out on smooth rolling glides and allows you to easily integrate your notebook computer with projectors and other equipment.
- Notebook shelf supports are arc welded to the leg supports for a strong and secure platform to support expensive computer equipment.
- Durable all-steel construction with black powder paint finish feature legs welded to the shelves so minimal assembly time is required.
- Includes a roomy lockable storage cabinet with two keys and a rear grommet hole for cord management.
- Rolls smoothly on 4" "Quiet Glide" casters, 2 locking.
- Die-pressed shelves have a 1/4" lip to prevent equipment from accidentally sliding off while in transport.
- Top shelf includes a ribbed rubber mat.
- Recommended for use with a projector and notebook computer or up to a 20" diagonal monitor.
- Optional electrical unit with a 20 foot extension cord and cord winder allows you to position your cart anywhere in the room and still reach an electrical outlet.
- CA2642NS series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. CA2642NS series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.



DIMENSIONS

Overall: 24" w x 18" d x 26-42" h

Top Shelf: 24" w x 18" d

Notebook Shelf: 20" w x 14" d, supports up to 15 lbs.

Notebook Shelf Height Clearance: 2-1/2" h

Middle to Notebook Shelf: 1"-13" h

Cabinet Interior: 23-1/2" w x 17-1/2" d x 15-1/2" h

COLOR & FINISH

Black (BK) powder paint

STANDARD EQUIPMENT

24" w x 18" d Shelves (1)

20" w x 14" d Notebook Shelf (1)

Lower cabinet section (1)

14" Glides (1 set)

1" round plastic caster insert (4)

4" diameter casters (4)

18" x 24" Rubber Mat (1)

Keys for cabinet lock (2)

2-outlet electrical unit (1) [CA2642NS-E4 only]

3-outlet electrical unit (1) [CA2642NS-M4 only]

WEIGHT AND FREIGHT CLASS

CA2642NS: 63 lbs.

CA2642NSE: 65 lbs.

CA2642NS-M4: 65 lbs.

Freight class 85. All available to ship via UPS

Ships ready to assemble in one (1) carton pack



ACCESSORIES

E-Unit Electrical assembly with 2 grounded outlets, 20 ft. grounded extension cord. Standard on CA2642NS-E4.

ES-Unit Electrical assembly with 3 grounded outlets, 20 ft. grounded extension cord. Standard on CA2642NS-M4.

4" CASTER CART CARTON DIMS & UPC CODE

26" w x 20" d x 32" h

CA2642NS: 0 96633 30477 6

CA2642NSE: 0 96633 30536 0

CA2642NS-M4: 0 96633 30479 0

5" CASTER CART CARTON DIMS & UPC CODE

26" w x 20" d x 32" h

CA2642NS-P5: 0 96633 30480 6

CA2642NS-E5: 0 96633 30481 3

CA2642NS-M5: 0 96633 30482 0

MADE IN THE USA

The CA2642NS adjustable cart is made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The CA2642NS adjustable carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. CA2642NS series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

SUGGESTED SPECIFICATIONS

CA2642NS Adjustable Cabinet Table has three (3) 20-gauge steel 18" x 24" shelves. Shelves are press formed with a 1/4" lip bordering the top surface on all four sides. The top shelf has a 20-gauge steel stiffener electrically welded underneath the surface front to back. A Black rubber mat 18" x 24" is placed on the top shelf. A 14" X 20" pull out notebook shelf pulls out from under the top shelf on 14" glides. The pull out shelf is mounted to two steel bars that are arc welded between the leg posts on the upper portion of the cart and supports up to 15 lbs. of equipment. Top shelf has two (2) 3/16" diameter holes centered on the right side, left side and rear to accept an optional electrical assembly. Table has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs 21-1/4" long welded to the shelf at each corner. Each leg has two (2) 1/4" diameter holes near the bottom of the section and in the center of the leg that will accept a 1/4-20 machine screw. The holes are spaced 4" apart to permit height adjustments of 26", 30", 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by the machine screw. The bottom section of the adjustable table consists of a 20-gauge steel cabinet of interior dimensions 23"W x 15-1/2"H x 17"D. There are four (4) 14-gauge steel 19" legs welded to the cabinet at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg that will accept a 1/4-20 machine screw. Holes are 4" apart to permit table height adjustments (as noted above). Cabinet has one (1) 20-gauge steel stiffener spot welded top to bottom. Model has a black powder paint finish. A hard plastic caster insert is mounted to each leg. Casters are mar-resistant Black hard rubber and 4" in diameter. Each caster assembly has ball bearing swivel capabilities and steel construction. Two (2) have locking brakes. Optional electrical assembly is completely enclosed with two (2) or three (3) grounded outlets. Includes 20 ft. 3-wire cord, cord winder, and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. CA2642NS Projector Cart ships assembled in one (1) carton and is able to ship via UPS.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETFORD.COM